



MITEL

5602 Wireless Phone

This compact wireless phone is designed specifically for the busy office environment, such as in hospitality, retail, and general offices, offering a full range of features and accessories at an attractive price. The Mitel® 5602 Wireless Phone has a large backlit graphical display, local phonebook, loudspeaker function, provides extensive talk time, and supports corporate directory access and SMS messaging capability.

- Graphical illuminated display
- Local phonebook
- Corporate phonebook (requires Mitel Wireless Services Messaging gateway)
- Call log
- Messaging / alert capable (receive)
- Vibrator alert
- Loudspeaker function
- Standard (2.5mm) headset connector
- Carrying clip
- Battery (up to 20 hours of talk time / up to 140 hours of standby time)
- Desktop charger (optional)



System features supported:

- Voice mail access with message waiting indication
- Hold / retrieve with music on hold
- Call forward
- Transfer
- Three party conference
- Call waiting and retrieve
- Do not disturb
- Call pickup
- Call park (slot number not specifiable)

5602 Wireless Phone Rack Charger

- For charging up to twelve handsets
- Requires a 5602 Wireless Phone rack charger power supply plus 5602 Wireless Phone rack charger modules
- Each rack charger power supply supports up to three rack charger models
- Each rack charger module supports charging four 5602 Wireless Phone handsets

Technical Specifications

Physical	
Dimensions (l x w x d)	143 x 53 x 26 mm (5.63 x 2.09 x 1.02 in)
Display (w x h)	101 x 80 pixel LCD with white LED back-light
Weight	131 g (0.29 lb) when battery is installed
Material	Case: PC / ABS
Key pad	Silicon rubber
Color	Grey and silver
Clip	Hinge type (standard), swivel clip (optional)
Battery and charging	
Type	850 mAh (Li-Ion)
Speech time	20 hours
Stand-by time	140 hours
Charge time	4 hours
Languages	
Eleven pre-installed (Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Portuguese, Spanish, Swedish) and one additional programmable	
Phonebook	
Max. 12 characters in a name and 24 digits in a number	

Telephony

Indication	Ring signal (14 preprogrammed plus 10 downloadable melodies configured by the Cordless Phone Manager CPM), flashing LED and vibrator
Answer call	Button press or auto-answer
Call list storage capacity	20 calls with time stamp (max. 10 dialed calls; max. 10 received / missed calls)

If a number occurs more than once, the last time stamp is shown together with the total number of occurrences.

Environmental

Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	-20°C to 55°C (-4° to 131°F)
Enclosure protection	IP 40, IEC 60529, test probe Ø 1 mm, force 1 N
Free fall test	IEC 60068-2-32, dropped 12 times from 1 m

Messaging

Maximum message length	160 characters
Storage capacity	20 messages (totally max. 19200 characters)

Audio

Ring signal	Adjustable in nine steps
Earpiece	Adjustable in ten steps
Maximum sound pressure level	93 dBA typical at 10 cm at highest volume

